

McIntireTM

F-Series Air Dryers

DRY AIR TECHNOLOGY



Model F-20

Features :


Refrigerant System

- All Stainless Steel Heat Exchanger Combining both Air-to-Air and Refrigerant-to-Air Circuitry
- Highly Efficient Hermetic Compressor
- Copper Tube and Aluminum Fin Condenser
- Constant Pressure Expansion Valve
- All Electrical Components Easily Accessible
- Universal CFC Free R-134a Refrigerant
- Handles Inlet Air Temperature up to 180°F


Air System

- Enhanced Condensate Separator Includes 40 Micron Sintered Bronze Filter
- Exiting Air is Reheated to Eliminate Downstream Condensation and Pipe Sweating
- Maximum Pressure Drop Less than 4 psi
- Automatic Float Drain


745 Clark Avenue, Bristol, CT 06010 Ph. 800-4-DRYAIR Fax 860-314-4500
Visit our website at www.mcintireco.com



Front View



Top View



Side View

REFRIGERANT SYSTEM

- ◇ All Stainless Steel Heat Exchanger Combining both Air to Air and Refrigerant to Air Circuitry
- ◇ Highly Efficient Hermetic Compressor
- ◇ Thermally Protected
- ◇ Rubber Mounted
- ◇ Copper Tube and Aluminum Fin Condenser
- ◇ Constant Pressure Expansion Valve
- ◇ All Electrical Components Easily Accessible
- ◇ Universal CFC Free R-134a Refrigerant

AIR SYSTEM

- ◇ Enhanced Condensate Separator Includes 40 Micron Sintered Bronze Filtration
- ◇ Exiting Air is Reheated to Eliminate Downstream Condensation
- ◇ Maximum Pressure Drop Less than 4 psi
- ◇ Automatic Float Drain

INSTRUMENTATION

- ◇ Power On/Off Switch and Integrated Light
- ◇ Refrigerant Suction Pressure Gauge

CABINET

- ◇ Powder Coated Textured Paint Finish
- ◇ Heavy Duty Metal Construction

ELECTRICAL

- ◇ Lowest Power Consumption
- ◇ Several Available Voltages (3)
- ◇ 6' Power Cord

McINTIRE MODEL NUMBER F-20

Specifications

Flow Capacity (1) SCFM 35°F-39°F Dew Point	20 (4)
Flow Capacity (1) SCFM 50°F Dew Point	25
Capacity (2) 2°C PDP M3/Hr. 10°C PDP	34 39
KW Input	.26
Refrigerant Compressor H.P. Rating	1/6
Condenser Type	Air Cooled
Cooling Air Flow	125 CFM
Voltage (3)	1 or 2
Air Line Connection In/Out	1/2" FPT
Drain Connection	3/8" OD
Height	Inches 13.56 mm. 344.40
Width	Inches 18.25 mm. 463.55
Length	Inches 12.69 mm. 322.33
Weight	Pounds 58 kg. 26

Standard Features

- △ Power On/Off Switch
- △ Refrigerant Suction Pressure Gauge
- △ 2 Year Compressor Warranty
- △ 5 Year Heat Exchanger Warranty

Optional Feature

- △ Electronic Timer Drain

- (1) Flow Rating based on design conditions of 100°F inlet air temperature, 100 psi, 100° ambient air temperature
- (2) Metric flow rating based on design conditions of 32°C inlet air temperature, 7 BARS, 32°C ambient air temperature, 220 volt, single or 3 phase, 50 Hz operation. 43°C absolute maximum ambient air temperature on air cooled units.
- (3) Voltage Code
1-115/1/60 or 100/1/50
2-208-230/1/60 or 220-240/1/50
- (4) Pressure drop rated under 4 PSI

**Your Source For All
Your Dry Air Needs**

