



NOTE: ELECTRICAL CONNECTION MUST BE HARD PIPED WITH AN EXTERNAL FUSED DISCONNECT SWITCH WITH PROPER OVERLOAD PROTECTION.

NOTE: CIRCUIT BOARD TIMER IS RATED FOR 120V/1PH/60HZ ONLY.

NOTE: DRYER FRAME MUST BE SUITABLE GROUNDED.

NOTE: PROVIDED CONTACTS ARE RATED FOR 120V, 3 AMPERES.

REV		DATE		BY		CHECKED		APPROVED		REVISION		DESCRIPTION	
A	5.07.01	12/27/19	REV A	REWORK IN AUTOCAB	CTG	CTG	CTG	CTG	CTG	CTG	CTG	CTG	CTG
<p>REVISIONS:</p> <p>1. REVISED TO ADD 120V COMMON JUMPER</p> <p>2. REVISED TO ADD 120V COMMON JUMPER</p> <p>3. REVISED TO ADD 120V COMMON JUMPER</p> <p>4. REVISED TO ADD 120V COMMON JUMPER</p>													
<p>DATE: 5.07.01</p> <p>TIME: 10:00 AM</p> <p>BY: CTG</p> <p>CHECKED: CTG</p> <p>APPROVED: CTG</p> <p>REVISION: 1</p> <p>DESCRIPTION: WIRING SCHEMATIC 120V REMOTE ALARM CONTACTS</p>													

4 3 2 1