



NOTE: ELECTRICAL CONNECTION MUST BE HARD PIPED WITH AN EXTERNAL FUSED DISCONNECT SWITCH WITH PROPER OVERLOAD PROTECTION.

NOTE: CIRCUIT BOARD TIMER IS RATED FOR 120V/1PH/60HZ ONLY.

NOTE: DRYER FRAME MUST BE SUITABLE GROUNDED.

NOTE: MAXIMUM VOLTAGE AND CURRENT ON PROVIDED CONTACTS ARE 120V, 3 AMPERES.

REV		DATE	DESCRIPTION	BY	CHKD
A	5.07.01	12/27/19	REV & REDRAWN IN AUTOCAD I.E. PART 'N'	CTG	
CUI		DATE	DESCRIPTION	BY	CHKD
5.07.01		12/27/19	REV & REDRAWN IN AUTOCAD I.E. PART 'N'	CTG	
CUI		DATE	DESCRIPTION	BY	CHKD
5.07.01		12/27/19	REV & REDRAWN IN AUTOCAD I.E. PART 'N'	CTG	
CUI		DATE	DESCRIPTION	BY	CHKD
5.07.01		12/27/19	REV & REDRAWN IN AUTOCAD I.E. PART 'N'	CTG	
CUI		DATE	DESCRIPTION	BY	CHKD
5.07.01		12/27/19	REV & REDRAWN IN AUTOCAD I.E. PART 'N'	CTG	

WIRING SCHEMATIC  
 REMOTE ALARM DRY  
 CONTACT LOCATION  
 DATE: 5.07.01  
 DRAWN BY: GAUGHAN  
 CHECKED BY: NTS  
 PART NO: WS-113